

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 668440

PRIMARY CORNER DESCRIPTION NW Cor. Govt Lot #3, Sec. 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6654)

Set ¼ sec. post from which
A Laurel 10" dia., bears N.50°W., 18 lks.
A Fir 18" dia., bears S.20°E., 50 lks.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6731)

(On "old" E. bdy. of sec. 13)
The ¼ sec. cor. on old E. bdy., established by Hathorn, located by reference to the original bearing trees, which are in agreement with the field notes, except that the W. tree is dead and fallen.

At exact corner point
Set an Iron post 3 ft. long, 1" dia., 27" in the ground for ¼ sec. cor. of original sec. 13, with brass cap marked:

¼ S13 |
1923

from which
A Fir 24" dia., bears S.66°W., 63 lks. dist. mkd. ¼ S13 BT. (New BT)
A Fir 40" dia., bears N.49°W., 29 lks. dist. mkd. ¼ S13 BT (new BT)

The marks are overgrown on the old BT intended in the original survey to refer to sec. 18, T30S R1E.

Douglas Co. Surveyors Office - John M. Powell, and crew - Setp. 23, 1971 - C.S. File 54/59-137

Found - 1923 GLO brass cap as marked in 1923.
40" D.Fir now 49", N.49°W., 19.1 ft., shows good scar.
24" D.Fir now stump, S.66°W., 41.6 ft. found some fragments of scribing.
New BT - 22" D.Fir S.35½°W., 21.8 ft. scribed ¼ S13 CS BT.
Cor. now lies about 75.0 ft. North of old cutting cor. Also, approx. 200 ft. East of draw.