

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6654)

Set post corners secs. 7, 18, 12 and 13, from which
A Fir 48" dia., bears S.70°W., 33 lks.
A Fir 9" dia., bears N.15°E., 15 lks.
A Fir 10" dia., bears S.10°E., 25 lks.
A Maple 12" dia., bears N.60°W., 35 lks.

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 16 Page(s) 6684)

(From the cor. secs. 12 & 13, N.81°20'W., 29.79 chs. dist.)
The old cor. of secs. 7, 12, 13 and 18 which is a post marked and witnessed as described by the surveyor general. I destroy all marks on this corner referring to T30S R1E.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6730)

(On "old" E. bdy. of sec. 12)
Proportional measurement.
Set an iron post 3 ft. long, 2" dia., 28" in the ground for cor. of original secs. 12 and 13, with brass cap marked:

T30S

S12

S13

R1W

1923

from which
A Fir 12" dia., bears S.8½°W., 283 lks. dist. mkd. T30S R1W S13 BT.
An Ash 12" dia., bears N.24¼°W., 174 lks. dist. mkd. T30S R1W S12 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Sept. 24, 1971 - C.S. File 54/59-135

Found - GLO brass cap at cor., properly mkd.
12" D.Fir now 20", S.8½°W., 186.1 ft., opened for scribe "3".
12" Ash now rotted, N.24°W., 114.8 ft. shows old axe work N.24½°W.
New BTs- 11" D.Fir S.43°W., 32.7 ft. scribed T30S R1W S13 CS BT.

(Cont. Next Page)

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 668500

PRIMARY CORNER DESCRIPTION NW Cor. Govt Lot #1, Sec. 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

10" D.Fir N.64°W., 36.0 ft. scribed T30S R1W S12 CS
BT.
This brass cap lies under 36" log.

Douglas Co. Surveyors Office - Gary L. Langlitz; R.B.
Kimberling; N.L. Livers - Feb. 1978 - C.S. File 59/46-20

Found - 1923 GLO brass cap on a 2" I.P. set 6" above ground
properly mkd.

A 12" now 20" D.Fir bears S.14°W., 190.6 ft. (Rec.
S.8½°W., 186.8 ft.) with scribing "3" in opened
bottom blaze of well healed double blaze.

A 12" now 19" Ash bears N.27°W., 118.0 ft. (Rec.
N.24¼°W., 114.8 ft.) with a partially healed
rotted out blaze. (OBT)

A 11" now 14' D.Fir bears S.39°W., 32.7 ft. (Rec.
S.43°W.) with scribing visible in partially
healed double blaze.

A 10" D.Fir bears N.61°W., 36.0 ft. (Rec. N.64°W.)
with scribing "T30S R1W S12 CS BT" in double
blaze.

Condition report only. No new monument or accessories.
Cor. was under a 24" log which has now been sawed away, in a
small seasonal easterly drainage.

Fd. OK, April 1986 by R. Geisler - C.S. File 63/34