

PRIMARY CORNER DESCRIPTION NW Cor. Govt Lot #3, Sec. 12

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6653)

- Set ¼ sec. post, from which
- A Fir 15" dia., bears N.10°W., 8 lks.
- A Cedar 9" dia., bears S.40°E., 10 lks.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6729-30)

(On "old" E. bdy. Sec. 12)
The ¼ sec. cor. on the old E. bdy. of sec. 12, established by Deputy Hathorn, located by reference to the original bearing trees, which are in agreement with the field notes.
At exact corner point (no iron post available)
Set a basalt stone 24x8x6 ins., 18" in the ground for ¼ sec. cor. of original sec. 12, marked ¼ S12 on W. face, from which

- A Cedar 12" dia., bears S.35°W., 15 lks. dist. mkd. ¼ S12 BT. (New BT)
- A Fir 28" dia., bears N.10°W., 8 lks. dist. mkd. ¼ S12 BT. (Old BT)

I obliterate marks on former bearing tree intended in the original survey to refer to sec. 7, T30S R1E.

Douglas Co. Surveyors Office - Gary L. Langlitz, Deputy - Mike Tompkins, crew - Sept. 16, 1976 - C.S. File 59/24

(This corner is located along the Willamette Meridian as surveyed in 1857 and later changed.)
Found - A Stone 24" x 8" x 6", firmly set, extending 8" above ground and leaning westerly, with faint "¼" chiseled on West face.

- An Orig. 1857 BT, a 15" now 34" D.Fir, alive with well healed blaze, bears N.10°W., 6.1 ft. (Rec. N.10°W., 5.2 ft.)
- An Orig. 1857 BT, a 9" now 14" I.Cedar, alive with "BT" visible on unhealed blaze bears S.40°E., 7.1 ft. (Rec. S.40°E., 6.6 ft.) Note: the markings on this tree were partially obliterated during the 1923 retracement survey.
- A 1923 BT, a 12' now 20" I.Cedar bears S.35°W., 8.8 ft. (Rec. S.35°W., 9.9 ft.) Alive and well healed. (Note: the origi. measurement fits this BT at breast height, not a ground level.)

At corner point, WE SET: A 1" x 30" I.P., 24" in the ground with the orig. stone along the West side, cap stamped:
(Cont. Next Page)

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 668540

PRIMARY CORNER DESCRIPTION NW Cor. Govt Lot #3, Sec. 12

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Douglas County Surveyor 1976
T 30 S R 1 W
¼ S 12