

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 16 Page(s) 6680)

Set a basalt stone 15x12x6 ins., 10" in ground for ¼ sec. corner, marked ¼ on W. face, from which

A Fir 30" dia., bears N.29°E., 22 lks. dist. mkd. ¼ S31 BT.

A Fir 20" dia., bears S.75°W., 14 lks. dist. mkd. ¼ S36 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6744)

The original ¼ sec. cor., which is a basalt stone, 12x6x5 ins. above ground, firmly set marked ¼ on W. face, hereafter this cor. will refer to sec. 36 only.

I mark the ¼ cor. stone S36 on W. face, from which

A Fir 30" dia., bears N.29°E., 22 lks. dist. I destroy marks on this tree.

A Fir 20" dia., bears S.75°W., 14 lks. dist. mkd. ¼ S36 BT. (Old BT)

A Fir 36" dia., bears N.23°W., 26 lks. dist. mkd. ¼ S36 BT. (New BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - Jan. 1968 - C.S. File 54/59-45

Found - 36" now 39" D.Fir N.28°W., (Rec. N.23°W.) 17.2 ft., shows good scar.

20" D.Fir now down, S.75°W., 9.2 ft. scribe visible "¼ S36 BT"

Set Brass cap at cor. mkd: County Surveyors Office

R	T 30 S	R
1 ¼	S 36	1
W	1968	E

New BTs- 26" D.Fir S.32°W., 29.5 ft. scribed ¼ S36 CS BT.

36" D.Fir N.28°W., 17.2 ft. tree OK, new bearing.

Corner lies 236.3 ft. South of cor. to secs. 30 & 31, T30-1E