

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 16 Page(s) 6681)

Set a basalt stone 15x12x10 ins., 10" in ground for ¼ sec. corner, marked ¼ on W. face, from which
A Fir 30" dia., bears N.12°E., 25 lks. dist. mkd. ¼ S30 BT
A Fir 30" dia., bears N.80°W., 33 lks. dist. mkd. ¼ S25 BT

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6745)

The original ¼ sec. cor., which is a basalt stone, 12x10x5 ins. above ground, firmly set, marked ¼ on W. face. Hereafter this cor. will refer to sec. 25 only. I mark the cor. stone ¼ S25 on W. face, from which
A Fir 30" dia., bears S.17°W., 35 lks. dist. mkd. ¼ S25 BT. (New BT)
A Fir 34" dia., bears N.80°W., 33 lks. dist. mkd. ¼ S25 BT. (Old BT)
I destroy the marks on the old BT in sec. 30.

Douglas Co. Surveyors Office - John M. Powell, and crew - Jan/Feb. 1968 - C.S. File 54/59-58

Found - No trace of stone at ¼ corner.
30" now 38" D.Fir S.17°W., 23.1 ft., opened for scribe "BT".
34" now 39" D.Fir N.80°W., 21.8 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office
R T 30 S R
1 S 25 ¼ 1
W 1968 E

BTs OK, tagged same.
Cor. lies approx. 340 ft. S. of logging road and 236.3 ft. South of Cor. 19 & 30 only, T30S R1E.