

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 16 Page(s) 6681)

Set a basalt stone 15x10x6 ins., 10" in ground for corner of secs. 24 and 25, marked with 4 notches on N. and 2 notches on S. edges, from which
A Fir 10" dia., bears S.30°W., 29 lks. dist. mkd. T30S R1W S25 BT.
A Fir 20" dia., bears N.2°W., 36 lks. dist. mkd. T30S R1W S24 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6745)

The cor. of secs. 24 and 25, which is a basalt stone 10x6x5 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. I mark the cor. stone S25 on SW., and S24 on NW. face.

Douglas Co. Surveyors Office - John M. Powell, and crew - June 1968 - C.S. File 54/59-111

Found - No trace of corner stone.
20" D.Fir, now down and burnt, N.2°W., 23.8 ft, found scribe.
10" D.Fir, now rotten stump, S.30°W., 19.8 ft.
Set Brass cap at cor. mkd: County Surveyors Office
R T 30 S R
1 S 24 | S 19 1
W S 25 | E
1968

New BTs- 10" D.Fir N.2°W., 27.4 ft. mkd. T30S R1W S24 CS BT
10" D.Fir S.29°W., 18.2 ft. mkd. T30S R1W S25 CS BT
14" D.Fir N.33°E., 10.4 ft. mkd. T30S R1E S19 CS BT
Cor. lies 236.3 ft. S. of ¼ sec. 19 only, T30S R1E.