

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 700304

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 19 only, T30-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6745-46)

Set an iron post 3 ft. long, 1" dia., 27" in the ground for ¼ sec. cor. of sec. 19 only, with brass cap mkd: ¼ S19
1923

from which

A Fir 50" dia., bears N.2°E., 356 lks. dist. mkd. ¼ S19 BT
A Madrona 6" dia., bears S.5°E., 233 lks. dist. mkd. ¼ S19 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - June 1968 - C.S. File 54/59-112

Found - GLO brass cap, properly mkd. in 1923.
50" now 60" D.Fir N.2°E., 235.0 ft., shows good scar
Found probable SE. BT, too many bees to check.
New BTs- 8" D.Fir S.16°E., 12.7 ft. mkd. ¼ S19 CS BT.
12" D.Fir N.17°E., 4.3 ft. mkd. ¼ S19 CS BT.
Cor. lies 236.3 ft. N. of sec. cor. to secs. 24 & 25 only,
T30S R1W.