

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 700344

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19 only, T30-1E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6746)

-----  
Set an Iron post 3 ft. long, 2" dia., 27" in the ground for the cor. of secs. 18 and 19 only, with brass cap marked:

T30S	T30S
R1W	S 18
S24	S 19
	R1E
	1923

from which

A Fir 22" dia., bears N.2°E., 62 lks. dist. mkd. T30S R1E S18 BT.

A Fir 17" dia., bears S.66°E., 18 lks. dist. mkd. T30S R1E S19 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - June/July 1968 - C.S. File 54/59-113

-----  
Found - Brass cap US GLO, properly marked in 1923.  
22" D.Fir now windfall, N.2°E., 40.9 ft., shows good face.

17" now 20" D.Fir S.66°E., 11.9 ft., shows good face.

New BT - 10" Cedar N.10°E., 28.3 ft. mkd. ¼ S30S R1E S18 CSBT  
The ¼ cor. of sec. 24 only, lies approx. 236 ft. South.