

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 16 Page(s) 6683-84)

Set a basalt stone 14x10x6 ins., 10" in ground for ¼ sec. corner, marked ¼ on W. face, from which
A Fir 30" dia., bears N.35°E., 15 lks. dist. mkd. ¼ S18 BT.
A Fir 30" dia., bears S.3°W., 46 lks. dist. mkd. ¼ S13 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6747)

The original ¼ sec. cor., which is a basalt stone, 10x6x5 ins., above ground, firmly set, marked ¼ on W. face. Hereafter, this cor. will refer to sec. 13 only. I mark the cor. stone ¼ S13 on W. face, from which
A Fir 30" dia., bears S.3°W., 46 lks. dist. mkd. ¼ S13 BT. (Old BT)
A Fir 36" dia., bears N.66°W., 64 lks. dist. mkd. ¼ S13 BT. (new BT)
I obliterate the marks on old BT in sec. 18.

Douglas Co. Surveyors Office - John M. Powell, and crew - June/July 1968 - C.S. File 54/59

Found - No trace of corner stone.
30" now 42" D.Fir, S.3°W., 30.4 ft., shows scar.
36" now 39" D.Fir N.66°W., 42.2 ft., opened for scribe "3".

Set Brass cap at cor. mkd: County Surveyors Office
R T 30 S R
1 S 13 ¼ | 1
W 1968 E

Bearing trees OK and tagged. Cor. is on steep, N. slope.