

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 700444

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 and 18, T30-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6747)

Set an Iron post 3 ft. long, 2" dia., 27" in the ground for cor. of secs. 7 and 18 only, with brass cap marked:

T30S		T30S
R1W		S 7
S13		S 18
		R1E
		1923

from which

A Fir 26" dia., bears N.64°E., 47 lks. dist. mkd. T30S R1E S7 BT.

A Fir 8" dia., bears S.62°E., 86 lks. dist. mkd. T30S R1E S18 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - June/July 1968 - C.S. File 54/59-107

Found - GLO brass cap, properly mkd. in 1923.

26" D.Fir now down, N.64°E., 31.0 ft.

8" D.Fir now 13" S.62°E., 56.8 ft.

New BT - 23" D.Fir N.63°E., 43.1 ft. mkd. T30S R1E S7 CS BT.
Cor. lies on steep South slope.