

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13 only (East)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 16 Page(s) 6684)

-----  
Set a basalt stone 15x12x12 ins., 10" in ground for cor. of secs. 12 and 13, marked with 2 notches on N. and 4 notches on S. edges, from which  
A Fir 12" dia., bears S.13°W., 106 lks. dist. mkd. T30S R1W S13 BT.  
A Pine 20" dia., bears N.48°W., 11 lks dist. mkd. T30S R1W S12 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6748)

-----  
The cor. of secs. 12 & 13 only, which is a basalt stone 15x6x5 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. I mark the cor. stone S13 on SW., and S12 on NW. face.

Douglas Co. Surveyors Office - John M. Powell, and crew - June/July 1968 - C.S. File 54/59-108

-----  
Found - Corner stone, out of place.  
12" now 24" D.Fir, S.13°W., 70.0 ft., shows good place.  
20" now 22" Pine, N.48°W., 7.3 ft., scribe visible.  
Set Brass cap at cor. mkd: County Surveyors Office  
R T 30 S R  
1 S 12 | 1  
W S 13 | E  
1968

BTs OK and tagged.  
Cor. lies 236.3 ft. S. of the ¼ cor. sec. 7, T30-1E.

Found OK by Ron Geisler, 4/1986 & 6/1986, C.S. File 63/34-8