

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 700544

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7 only, T30-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6748-49)

Set an Iron post 3 ft. long, 2" dia., 27" in the ground for cor. of secs. 6 and 7 only, with brass cap marked:

T30S		T30S
R1W		<u>S 6</u>
S13		S 7
		R1E
1923		

from which

A Fir 22" dia., bears N.67°E., 85 lks. dist. mkd. T30S R1E S6 BT.

A Fir 48" dia., bears S.75°E., 21 lks. dist. mkd. T30S R1E S7 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - June/July 1968 - C.S. File 54/59-102

Found - No trace of brass cap.

22" W.Fir now stump, N.67°E., 56.1 ft., opened for scribe "6 BT."

48" D.Fir now uproot stump, S.75°E., 26.6 ft. (Rec. 13.9 ft.), opened for scribe "T30S"

Chained distance of 248.2 ft. between ¼ sec. 12 and sec. cor. distance falls in uprooted stumps. Dug for old brass cap but not found.

Set Brass cap at cor. mkd:

County Surveyors Office

R	T 30 S	R
1	S 12 <u>S 6</u>	1
W	S 7	E
1968		

New BTs- 8" W.Fir S.8°E., 5.0 ft. mkd. T30S R1E S7 CS BT.

8" D.Fir N.5°E., 82.7 ft. mkd. T30S R1E S6 CS BT.

14' D.Fir N.10°W., 23.5 ft. mkd. T30S R1W S12 CS BT