

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only (East)

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 16 Page(s) 6685)

Set a basalt stone 20x14x10 ins. 15" in ground for corner of secs. 1 and 12, marked with 1 notch on N. and 5 notches on S. edges, from which

A Hemlock 16" dia., bears S.37°W., 21 lks. dist. mkd. T30S R1W S12 BT.

A Fir 10" dia., bears N.72°W., 61 lks. dist. mkd. T30S R1W S1 BT.

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6749)

The cor. of 1 and 12 only, which is a basalt stone, 12x8x5 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. Bot old bearing trees are dead. I mark the stone S12 on SW., and S1 on NW. face, from which

A Fir 8" dia., bears S.18°W., 49 lks. dist. mkd. T30S R1W S12 BT. (New BT)

A Cedar 24" dia., bears N.31°W., 129 lks. dist. mkd. T30S R1W S1 BT. (New BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - June 1968 - C.S. File 54/59-104

Found - 24" now 26" Cedar stump N.31°W., 88.1 ft., scribe visible "T30".

No trace of corner stone or SW. BT.

Corner in heavily logged area.

Set Brass cap at cor. mkd: County Surveyors Office

R	T 30 S	R
1	S 1	1
W	S 12	S6 E
1968		

New BTs- 5" D.Fir N.40°W., 19.0 ft. mkd. S1 CS BT.

5" D.Fir N.65°W., 19.5 ft. mkd. S1 CS BT.

No other trees available.

Corner lies 248.0 ft. S. of ¼ cor. sec. 6 only, T30-1E.