

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 700604

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 6 only, T30-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6749)

Set an iron post 3 ft. long, 1" dia., 27" in the ground for 1/4 sec. cor. of sec. 6 only, with brass cap mkd: | 1/4 S6
1923

from which

A Fir 10" dia., bears N.71°E., 17 lks. dist. mkd. 1/4 S6 BT.
A Hemlock 10" dia., bears S.30°E., 5 lks. dist. mkd. 1/4 S6 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - June/July 1968 - C.S. File 54/59-103

Found - No trace of brass cap nor SE. BT. Corner falls in old skid road.
10" now 13' D.Fir N.71°E., 11.2 ft. opened for scribe "BT"

Set Brass cap at cor. mkd: County Surveyors Office
R T 20 S R
1 | 1/4 S 6 1
W | E
1968

Reblazed and rescribed:

13" D.Fir N.71°E., 11.2 ft. mkd. 1/4 S6 CS BT.
New BT - 20" W.Fir S.60°E., 13.4 ft. mkd. 1/4 S6 CS BT.
Corner lies 248.0 ft. N. of sec. cor. 1 & 12, T30-1W.