

TOWNSHIP 30 RANGE 02E POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION Twp Cor. T30-2E & T31-2E (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Peter Applegate, US Deputy Surveyor under contract #571 dated April 10, 1891 - (DCSO records Vol. 26 Page(s) 11252-3)

Set a stone 14x10x10", 9" in the ground for cor. to Twp. 30 & 31S, Rs 1 & 2 E mkd with 6 notches on each edge, from which
A hemlock, 12" dia., bears N.57°W., 7 lks., mkd: T30S R1E S36 BT.
A R.Fir, 16" dia., bears S.61°W., 28 lks., mkd: T31S R1E S1 BT.
A R.Fir, 18" dia., bears N.32°E., 16 lks., mkd: T30S R2E S31 BT.
A W.Fir, 18" dia., bears S.39°E., 57 lks., mkd: T31S R2E S6 BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor, under Group No. 175, surveyed Sept/Nov 1936 - (DCSO Vol. 56 Page(s) 17629)

The old cor. of Tps 30 & 31 S., Rs. 1 & 2 E., which is a porphyry stone, 24x9x8", loosely set, mkd with 6 notches on N & W edges.
I change this cor. to refer to T30 & 31S., R2E only.
At point for cor.
Set an iron post, 3' long, 3" dia., 27" in the ground, for cor. of Tps 30 & 31 S, R 2 E., with brass cap marked:

		T30S	
T30S		R 2 E	
R 1 E		<u>S 31</u>	
		S 6	
S 36		T31S	
		1936	

from which
A fir, 22" dia., bears N.32°E., 17 lks., blaze healed; I do not open. I reblaze and re-mark this tree T30S R2E S31 BT. (Old BT)
A W.Fir, 20" dia., bears S.39°E., 58 lks. blaze healed; I do not open (Old BT)
A fir, 22" dia., bears S.61°W., 30 lks., mkd: T31S R1E S1 BT. I obliterate the marks (Old BT)
A hemlock, 20" dia., N.57°W., 7 lks., mkd. in partially decayed blaze 30 1 E 3. I obliterate the marks (Old BT)
A W.Pine, 47" dia., bears S.61°E., 85 lks., mkd: T31S R2E S6 BT. (New BT)