

TOWNSHIP 30 RANGE 02E POINT IDENTIFIER # 138100

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 6 only; T31-2E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Peter Applegate, US Deputy Surveyor under contract #571 dated April 10, 1891 - (DCSO records Vol. 26 Page(s) 11133)

Set a stone 14x12x8" 9" in the ground for ¼ S cor. marked ¼ on N face.
from which
A R.Fir, 36" dia., bears N.54°E., 15 lks., mkd: ¼ S BT.
A larch, 36" dia., bears S.54°W., 3 lks., mkd: ¼ S BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transit man, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Page(s) 21852)

The orig. ¼ sec. cor. of secs. 6 & 31, which is a sandstone, 16x12x8", firmly set, with no legible, marks.
I now change this cor. to refer to sec. 6 only.
At point for cor.
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, with the orig. stone deposited at the base for ¼ sec. cor. of sec. 6 only, with brass cap marked: ¼ S 6
1937 from which
A fir, 47" dia., bears N.54°E., 16 lks., mkd: ¼ S BT. I obliterate the marks on this tree. (Old BT)
A fir, 40" dia., bears S.54°E., 7 lks. blaze healed. I do not open. (Old BT)
A fir, 10" dia., bears S.66°E., 66 lks. mkd: ¼ S6 BT. (New BT)
A fir, 7" dia., bears S.81°W., 105 lks. mkd: ¼ S6 BT (New BT)
(S.89°06'E., 2.21 chains to S¼ S31 only)