

TOWNSHIP 30 RANGE 02E POINT IDENTIFIER # 141700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 31 only; T29-2E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated 1920 - (DCSO records Vol. 25 Page(s) 10690 & Vol. 26 Page(s) 11151)

Set an iron post, 3 ft. long, 1" dia., 12" in the ground, to bed rock, (supported by a mound of stone, 3 ft. base, 1½ ft. high, around post) with brass cap marked

¼ $\frac{S\ 31}{S\ 6}$
1923

from which

An Oak, 9" dia., bears N.42°W., 65 lks., mkd: ¼ S31 BT.

An Oak, 6" dia., bears S.14°W., 23 lks., mkd: ¼ S6 BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transitman, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Pages 21858-9)

The orig. ¼ sec. cor. of secs. 6 & 31, which is an iron post, 1" dia., 9" above the top of a mound of stone, 3 ft. base, 1½ ft. high, firmly set, with marks on brass cap conforming to the record.

I now change this cor. to refer to sec. 31 only and remark the brass cap as follows:

¼ $\frac{S\ 31}{1923}$

from which

An Oak, 9" dia., bears N.42°W., 65 lks., mkd: ¼ S31 BT.
(Old BT)

An Oak, 6" dia., bears S.14°W., 23 lks., mkd: ¼ S6 BT. I obliterate the marks on this tree (Old BT)

A fir, 25" dia., bears N.73°E., 105 lks., mkd: ¼ S31 BT.
(New BT)