

PRIMARY CORNER DESCRIPTION Cor. Secs. 5 & 6 only; T31-2E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Peter Applegate, US Deputy Surveyor under contract #571 dated April 10, 1891 - (DCSO records Vol. 26 Page(s) 11133-4)

Set a stone 14x10x8", 10" in the ground for cor. of secs. 5, 6, 31, & 32 mkd with one notch on W & 5 notches on E side, from which

- A W.Fir, 18" dia., bears N.18°E., 44 lks., mkd: T30S R2E S32 BT.
- A R.Fir, 30" dia., bears N.66°W., 39 lks., mkd: T30S R2E S31 BT.
- A R.Fir, 24" dia., bears S.20°E., 40 lks., mkd: T31S R2E S5 BT.
- A R.Fir, 14" dia., bears S.50°W., 45 lks., mkd: T31S R2E S6 BT.

Land somewhat broken, West part East half nearly level.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transit man, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Page(s) 21851)

The orig. cor. of secs. 5, 6, 31, & 32, which is a basalt stone, 15x15x10", firmly set, mkd. with cross (X) on top. I now change this cor. to refer to secs. 5 & 6 only.

At point for corner,

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, with the orig. stone deposited at the base, for cor. of secs. 5 & 6 only, with brass cap marked:

T30S R2E
 S 31
S 6 | S 5
T31S R2E
1937

from which

- A fir snag, 22" dia., bears N.18°E., 46 lks., mkd T30S R2E S32 BT. I obliterate the marks on this tree. (Old BT)
- A fir, 37" dia., bears S.20°E., 39 lks., blaze healed. I do not open (Old BT)
- A fir, 38" dia., bears S.50°W., 43 lks., blazed healed. I do not open (Old BT)
- A fir, 47" dia., bears N.66°W., 43 lks., mkd. on bark, T30S R2E S31 BT. I obliterate the marks on this tree. (Old BT)

(S.89°14'E., 2.12 chains to Sec. Cor. Secs. 31 & 32, T30-2E)