

TOWNSHIP 30 RANGE 02E POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Cor. Secs. 5 & 6 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transitman, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Page(s) 21922)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground for closing cor. of secs. 5 & 6, with brass cap mkd:

T29S R2E  
S 31  
S 6 | S 5  
T30S | R2E  
C C  
1937

from which

A W.Fir, 15" dia., bears S.30°E., 68 lks., mkd: T30S R2E  
S5 CC BT.

A W.Fir, 23" dia., bears S.58°W., 74 lks., mkd: T30S R2E  
S6 CC BT.

From point of intersection the cor. of secs. 31 & 32 only, S. bdy. T29-2E previously described, bears S.89°57'E., 0.44 chs.