

TOWNSHIP 30 RANGE 02E POINT IDENTIFIER # 201700

PRIMARY CORNER DESCRIPTION Cor. Secs. 31 & 32, South; T29-2E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated 1920 - (DCSO records Vol. 25 Page(s) 10690 & Vol. 26 Page(s) 11150)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 5, 6, 31, & 32, with brass cap mkd

T29S R2E
S 31|S 32
S 6|S 5
T 30 S
1923

from which

- An Alder, 8" dia., bears N.79°E., 15 lks., mkd: T29S R2E S32 BT.
- An Alder, 10" dia., bears S.44°E., 36 lks., mkd: T30S R2E S5 BT.
- A fir, 24" dia., bears S.61°W., 58 lks., mkd: T30S R2E S6 BT.
- An Alder, 10" dia., bears N.16°W., 37 lks., mkd: T29S R2E S31 BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transitman, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Page(s) 21858)

The orig. cor. of secs. 5, 6, 31, & 32, which is an iron post, 2" dia., 12" above ground, firmly set, with marks on brass cap conforming to the record.

I now change this cor to refer to secs 31 & 32 only & re-mark the brass cap as follows:

T29S R2E
S 31|S 32
T30S R2E
S 5
1923

from which

- An Alder, 8" dia., bears N.79°E., 15 lks., mkd: T29S R2E S32 BT. (Old BT)
- An Alder, 10" dia., bears S.44°E., 36 lks., mkd: T30S R2E S5 BT. I obliterate the marks on this tree. (Old BT)
- A fir, 24" dia., bears S.61°W., 58 lks., mkd: T30S R2E S6 BT. I obliterate the marks on this tree. (Old BT)
- An Alder, 10" dia., bears N.16°W., 37 lks., mkd: T29S R2E S31 BT. (Old BT)