

TOWNSHIP 30 RANGE 02E POINT IDENTIFIER # 239100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 5 only, North; T31-2E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Peter Applegate, US Deputy Surveyor under contract #571 dated April 10, 1891 - (DCSO records Vol. 26 Page(s) 11134)

-----  
Set a stone 12x8x8", 8" in the ground for ¼ sec. cor. mkd. ¼ on North face, from which  
A cedar, 24" dia., bears S.30°E., 32 lks., mkd: ¼ S BT.  
A W.Fir, 18" dia., bears N.47°E., 51 lks., mkd: ¼ S BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transit man, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Page(s) 21850)

-----  
The orig. ¼ sec. cor. of secs. 5 & 32, which is a basalt stone, 14x10x8", firmly set, mkd. with cross (X) on top. I now change this cor. to refer to sec. 5 only.  
At point for corner.  
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, with the orig. stone deposited at the base, for the ¼ sec. cor. of sec. 5 only, with brass cap mkd.

¼ S 5  
1937

from which  
A W.Fir, 27" dia., bears N.44°E., 49 lks., mkd: ¼ S BT. I obliterate the marks on this trees (Old BT)  
A cedar, 30" dia., bears S.36°E., 32 lks., blaze healed. I do not open (Old BT)  
A W.Fir, 8" dia., bears S.29°W., 20 lks., mkd. ¼ S5 BT (New BT)  
(S.89°01'E., 1.96 chains to South ¼ corner Sec. 32)