

TOWNSHIP 30 RANGE 02E POINT IDENTIFIER # 241700

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 32; T29-2E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated 1920 - (DCSO records Vol. 25 Page(s) 10689 & Vol. 26 Page(s) 11149-50)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 S 32
S 5
1923

from which

- A pine, 20" dia., bears N.84°W., 42 lks., mkd: 1/4 S32 BT.
- A fir, 24" dia., bears S.49°W., 12 lks., mkd: 1/4 S5 BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transitman, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Page(s) 21857)

The orig. 1/4 sec. cor. of secs. 5 & 32, which is an iron post, 1" dia., 9" above ground, firmly set, with marks on the brass cap conforming to the record.

I now change this cor. to refer to sec. 32 only & remark the brass cap as follows:

1/4 S 32
1923

from which

- A pine, 22" dia., bears N.68°W., 42 lks., mkd: 1/4 S32 BT. (Old BT)
- A fir, 24" dia., bears S.45°W., 12 lks., mkd: 1/4 S5 BT. I obliterate the marks on this tree. (Old BT)
- A fir, 20" dia., bears N.63°E., 30 lks., mkd: 1/4 S32 BT. (New BT)