

TOWNSHIP 30 RANGE 02E POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs 8, 9, 16, & 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transitman, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Page(s) 21904)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 8, 9, 16, & 17, with brass cap mkd

T30S R2E  
S 8 | S 9  
S 17 | S 16  
1937

from which

- A fir, 25" dia., bears N.35°E., 136 lks., mkd: T30S R2E S9 BT.
- A fir, 68" dia., bears S.22°E., 129 lks., mkd: T30S R2E S16 BT.
- A W.Fir, 30" dia., bears S.63°W., 169 lks., mkd: T30S R2E S17 BT.
- A fir, 23" dia., bears N.63°W., 139 lks., mkd: T30S R2E S8 BT.