

TOWNSHIP 30 RANGE 02E POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor Secs 4, 5, 8, & 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transitman, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Page(s) 21906)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 4, 5, 8, & 9, with brass cap mkd

T30S R2E  
S 5 | S 4  
S 8 | S 9  
1937

from which

- A pine, 19" dia., bears N.29°E., 74 lks., mkd: T30S R2E S4  
BT.
- A fir, 17" dia., bears S.68°E., 49 lks., mkd: T30S R2E S9  
BT.
- A fir, 3" dia., bears S.50°W., 64 lks., mkd: BT.
- A fir, 14" dia., bears N.46°W., 25 lks., mkd: T30S R2E S5  
BT.