

PRIMARY CORNER DESCRIPTION Cor. Secs. 32 & 33 only; T29-2E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated 1920 - (DCSO records Vol. 25 Page(s) 10688-9 & Vol. 26 Page(s) 11149)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 4, 5, 32, & 33, with brass cap mkd

T29S R2E
S 32|S 33
S 5|S 4
T30S
1923

from which

- A fir, 24" dia., bears N.2°E., 53 lks., mkd: T29S R2E S33 BT.
- A cedar, 7" dia., bears S.61°E., 57 lks., mkd: T30S R2E S4 BT.
- A fir, 9" dia., bears S.16°W., 47 lks., mkd: T30S R2E S5 BT.
- A cedar, 40" dia., bears N.87°W., 127 lks., mkd: T29S R2E S32 BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transitman, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Pages 21856-7)

The original cor. of secs. 4, 5, 32, and 33, which is an iron post, 2" dia., 9" above grounds. firmly set, with marks conforming to the record.

I now change this cor. to refer to secs. 32 and 33 only and re-mark the brass cap as follows:

T29S R2E
S 32|S 33
T30S
S 4
1923

from which

- A fir, 24" dia., bears N.2°E., 53 lks., mkd: T29S R2E S33 BT. (Old BT)
- A cedar, 7" dia., bears S.61°E., 57 lks., mkd: T30S R2E S4 BT. I obliterate the marks on this tree (Old BT)
- A fir, 9" dia., bears S.16°W., 47 lks., mkd: T30S R2E S5 BT. I obliterate the marks on this tree (Old BT)
- A cedar, 40" dia., bears N.87°W., 127 lks., mkd: T29S R2E S32 BT. (Old BT)