

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec 4, south, only; T31-2E

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Peter Applegate, US Deputy Surveyor under contract #571 dated April 10, 1891-(DCSO rec Vol 26 Pg 11135)

Set a stone for ¼ S cor. 12x12x6", 8" in the ground on summit of Umpqua divide, mkd. ¼ on N face, from which
A larch, 24" dia., bears S.16°W., 15 lks., mkd: ¼ S BT.
A larch, 36" dia., bears N.22°W., 10 lks., mkd: ¼ S BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transit man, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Pages 21848-9)

The orig. ¼ sec. cor. of secs. 4 & 33, which is a sandstone, 12x10x5" firmly set, mkd. ¼ on N face.

I now change this cor. to refer to sec. 4 only.
At point for corner,
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, with the orig. stone deposited at the base, for ¼ sec. cor. of sec. 4 only, with brass cap mkd:

¼ S 4
1937

from which
A W.Fir snag, 30" bears S.50°E., 17 lks. mkd. ¼ S (Old BT)
A W.Fir, 27" dia., bears S.30°E., 85 lks mkd: ¼ S4 BT. New
A W.Fir, 28" dia., bears S.1°W., 77 lks. mkd: ¼ S4 BT. New
Abbott Butte Lookout, bears N.43°03'E.
(S.89°09'E., 1.44 chains to South ¼ Cor. Sec. 33)

Jackson Co. Surveyors Office - B. Malotte and R Frost - June 1978 - C.S. File 58/183-14

Found - Bent over, the 1" iron pipe with properly marked GLO brass cap recorded by L. Carter in 1937. I removed, straightened and re-set said pipe in the orig. hole, (now projects 10")
The center of fir stump remains of orig. BT recorded by P. Applegate in 1891 and noted by Carter bears Record S.50°E., 11.22 ft.
Sawed Shasta R.Fir stump, 36" with healed blaze bears S.30°E., 56.10 ft.
Sawed Shasta R.Fir stump, 40" bears S.1°W., 52.20 ft. to center (Rec. S.1°W., 50.82 ft.)
New BTs- 12" Shasta R.Fir bears S.38°W., 28.80 ft.
16" Hemlock bears N.25°W., 30.70
Corner lies about 350 ft. East of location marker on 36" Shasta R.Fir, located alongside road, C. N-S.