

TOWNSHIP 30 RANGE 02E POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION ¼ Cor. Sec. 33 only South

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transit man, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Page(s) 21848)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor. of sec. 33 only, with brass cap mkd:

¼ S 33
1937

from which

A W.Fir, 25" dia., bears N.25°E., 47 lks., mkd: ¼ S33 BT.

A W.Fir, 35" dia., bears N.55°W., 84 lks., mkd: ¼ S33 BT.
(N.89°09'W., 1.44 chains to South ¼ Cor. Sec. 33)

Jackson Co. Surveyors Office, Ed McGinty, Co. Surveyor - B. Malotte - 6/12/1978 - C.S. File 58/183-5

Found - Projecting 9" (23 cm), the 1" (2.5 cm) dia. iron pipe with GLO brass cap (properly) mkd:

Bearing trees recorded by Carter fd as follows:

Sawed Shasta red fir stump, 30" (76 cm) dia., brs N.25°E., 30.05 ft. (9.16 m) to center. Record; N.25°E., 31.02 ft. (9.45 m).

Shasta red fir, 37" (94 cm) dia., with healed single blaze, brs. record; N.55°W., 55.44 ft. (16.90 m) to center.

I mk a new tree CS-BT:

Hemlock, 6" (15 cm) dia., brs. N.40°E., 13.10 ft. (3.99 m) to center of tree at lower blaze.