

TOWNSHIP 30 RANGE 02E POINT IDENTIFIER # 341700

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 33 only; T29-2E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated 1920 - (DCSO records Vol. 25 Page(s) 10688 & Vol. 26 Page(s) 11148)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 S 33
S 4
1923

from which

- A fir, 13" dia., bears N.7°E., 47 lks., mkd: 1/4 S33 BT.
- A fir, 6" dia., bears S.47°W., 63 lks., mkd: 1/4 S4 BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transitman, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Page(s) 21856)

The orig. 1/4 sec. cor. of secs. 4 & 33, which is an iron post, 1" dia., 10" above ground, firmly set, with marks conforming to the record.

I now change this cor. to refer to sec. 33 only and remark the brass cap as follows:

1/4 S 33
1923

from which

- A fir, 13" dia., bears N.7°E., 47 lks., mkd 1/4 S33 BT. (Old BT)
- A fir, 6" dia., bears S.47°W., 63 lks., mkd. 1/4 S4 BT.
I oblterate the marks on this tree. (Old BT)
- A fir, 27" dia., bears N.40°W., 79 lks., mkd. 1/4 S33 BT. (New BT)