

PRIMARY CORNER DESCRIPTION Cor. Secs. 3 & 4 only, T31-2E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Peter Applegate, US Deputy Surveyor under contract #571 dated April 10, 1891 - (DCSO records Vol. 26 Page(s) 11135)

Set a stone 14x10x8", 10" in the ground for cor. of secs. 3, 4, 33, & 34 mkd with 3 notches on E & 3 notches on W edges, from which

- A larch, 96" dia., bears N.50°W., 11 lks., mkd: T30S R2E S33 BT.
- A larch, 24" dia., bears S.38°W., 69 lks., mkd: T31S R2E S4 BT.
- A W.Fir, 24" dia., bears N.35°E., 31 lks., mkd: T30S R2E S34 BT.
- A W.Fir, 36" dia., bears S.10°E., 41 lks., mkd: T31S R2E S3 BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transit man, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Pages 21847-8)

The orig. cor. of secs. 3, 4, 33, & 34, which is a basalt stone, 14x10x8", firmly set, with no legible marks.

I now change this cor. to refer to secs. 3 & 4 only.

At point for corner,

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, with the orig. stone deposited at the base, for cor. of secs. 3 & 4, with brass cap mkd:

T30S	R2E
S 33	

S 4	S 3
T31S	R2E
1937	

from which

- A W.Fir, 25" dia., bears N.32°E., 32 lks., mkd: T30S R2E S34 BT. I obliterate the marks on this tree. (Old BT)
- A W.Fir 45" dia., bears S.7°E., 44 lks., blaze healed. I do not open. (Old BT)
- A W.Fir 40" dia., bears S.41°W., 81 lks., blaze healed. I do not open. (Old BT)
- A badly decayed W.Fir stump, 57" dia., bears N.50°W., 14 lks. (Old BT)

(S.88°49'E., 1.24 chains to CC Secs. 33 & 34)

Jackson Co. Surveyors Office - B. Malotte and R Frost - May 1978 - C.S. File 58/183-12

Found - 1937 GLO brass cap properly marked, lying on top of the ground as recorded by L. Carter.
continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 33 & 34 only, T31-2E

Alias	Description
Alias	Description
Alias	Description
Alias	Description

I re-set this pipe (in the hole it originally occupied) 28" in the ground alongside the original 16x12x7" stone. (Rec. 14x10x8" marked with 3 grooves on opposite sides.
The base of a tipped over fir, 30" containing scribed "T30S" in partially axed out face bears as recorded by Carter; N.32°E., 21.12 ft. He reports obliterating marks on this tree in 1937. Sawed fir stump, 58" bears as recorded by Carter, S.7°E. , 29.04 ft to center.
46" Shasta R.Fir with healed blazes, bears record (Carter) S.41°W., 53.46 ft. to center of tree. Stump hole fd. at record location of original NW BT. The brass cap corner of sections 33 and 34 bears S..87½°E., 82.73 ft. (Rec. S.88°49'E., 81.84 ft.) I mound stones around corner and mark a new tree CS BT:
29" W.Fir bears N.26¾°W., 38.36 ft. to center of tree at lower blaze.
Corner lies at NW edge of old skid road.

Jackson Co. Surveyors Office - Kerry K. Bradshaw, Co. Surveyor - B. Berman & H Durkee - July 15, 2009 (filed DCSO 8/24/2012) - C.S. File 65/77-23

Found - At corner position, exposed 10", the 2" dia. galv. iron pipe with a 2½" dia. brass cap set by Carter of the GLO in 1937 and (properly) marked. Original BTs recorded by Applegate of the GLO in 1891 fd with healed blazes & measured to center at base; S. fir rotted snag brs. record S.7°E., 29.0 ft. S. fir snag brs. record S.41°W., 53.5 ft. 1937 GLO BC for Sec.s 33 and 34 of T30S R2E brs. record S.87½°E., 82.7 ft. BT recorded on 1st re-establishment in 1978 fd w/healed double blazes & measured to center at lower blaze: W. fir snag brs. record N.26¾°W., 38.4 ft. Marked new BTs "CS""BT" and measured to center at lower blaze:
Cedar 6" dia. brs. S.31¾°E., 7.4 ft.
Cedar 8" dia. brs. S.42°W, 16.2 ft.
Note - Corner lies approx. 300 ft. east of old faint road to survey shelter.
Compass decl. 16°30' E.