

PRIMARY CORNER DESCRIPTION CC Secs. 33 & 34 only, South

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transit man, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Page(s) 21847)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground for cor. of secs. 33 & 34, with brass cap mkd:

T30S R2E
S 33|S 34
T31S R2E
S 3
1937

from which

A W.Fir, 55" dia., bears N.25°E., 52 lks., mkd: T30S R2E S34 BT.

A W.Fir, 55" dia., bears N.45°W., 30 lks., mkd: T30S R2E S33 BT.

(N.88°49'W., 1.24 chains to CC Secs. 33 & 34)

Jackson Co. Surveyors Office, Ed McGinty, Co. Surveyor - B. Malotte - R. Frost - 5/22/1978 - C.S. File 58/183-6

Found - Projecting 6", the 2" dia. iron pipe with GLO brass cap (properly) mkd.

The single remaining original BT:

A Shasta Red Fir, (record; W.Fir) now 56" dia., scribed "30S R2E S34 BT" in partly exposed face, brs. N.25°E., 32.83 ft. to scribed face. Record; N.25°E., 34.32 ft.

The brass cap corner of Sections 3 and 4, brs. N.87½°W., 82.73 ft. Record; N.88°49'W., 81.84 ft.

Mkd. a new tree "C.S. B.T.":

W.Fir, 33" dia., brs. N.26¾°W., 48.63 ft. to center of tree at lower blaze.

Corner lies about 1100 ft. East of USFS wood line crossing marker on 30" dia. Fir alongside road.