

PRIMARY CORNER DESCRIPTION Cor Secs 27, 28, 33, & 34

Alias	Description

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transitman, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Page(s) 21889)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 27, 28, 33, & 34, with brass cap mkd

T30S	R2E
S 28	S 27
S 33	S 34

1937

from which

- A W.Fir, 25" dia., bears N.52°E., 16 lks., mkd: T30S R2E S27 BT.
- A W.Fir, 50" dia., bears S.65°E., 157 lks., mkd: T30S R2E S34 BT.
- A fir, 13" dia. bears S.23°W., 31 lks mkd: T30S R2E S33 BT
- A fir, 38" dia. bears N.23°W., 89 lks mkd: T30S R2E S28 BT

Jackson Co. Surveyors Office, Ed McGinty, Co. Surveyor - B. Malotte - R. Frost - 8/22/1978 - C.S. File 58/183-6

Found - Projecting 9" (23 cm) in mound of stone (MOS) the original 2" (5cm) dia. iron pipe with standard GLO brass cap (properly) mkd:

Original BTs fd. As follows:

- Sawed fir stump, 25" (64 cm) dia., brs. N.48°E., 10.75 ft. (3.28 m) to center. Record; N.52°E., 10.56 ft. (3.22 m).
- Sawed fir stump, 63" (160 cm) dia., brs. record S.65°E., 103.62 ft. (31.58 m) to center.
- Hemlock, 18" (46 cm) dia., with healed single blaze, brs. S.23°W., 20.15 ft. (6.14 m) to center. Record; S.23°W., 20.46 ft. (6.24 m)
- Hemlock, 41" containing scribe marks including "S 28 BT" healed face, brs. N.23°W., 57.9 ft. (17.65 m) to center. Record; N.23°W, 58.74 ft. (17.90 m)

I mk new trees CS BT and take measurements to center of trees at lower blaze:

- Hemlock, 16" (41 cm) dia., brs. N.24°E., 68.73 ft. (20.95 m).
- Shasta red fir, 22" (56 cm) dia., brs. S.55°E. 44.90 ft. (13.69 m).

Corner lies 54 ft. (16.5 m) East of road c S.10°E., and 56 ft. (17.07 m) West of small stream.

TOWNSHIP 30 RANGE 02E POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Jackson Co. Surveyors Office, Roger R. Roberts, Co. Surveyor
- H. Durkee - B. Berman - July 24, 2008 (filed in Douglas Co.
7/11/2012) - C.S. file 65/77-8

Found - At the corner position, exposed 15" in a mound of
stones, the 2" dia. galv. iron pipe with a 2½"
dia. brass cap set by the GLO in 1937, (properly)
marked.

BTs recorded by L. Carter of the GLO in 1937, fd and measured
to center at base:

Hemlock snag with a healed blaze brs. record;
S.23°W., 20.2 ft.

Hemlock snag with scribe marks "S28 BT" in partially
healed blaze brs. N.23°W., 58.5 ft. Rec: 57.9 ft.

BTs recorded on 1st Re-establishment in 1978 found with
healed double blazes and measured to center at lower blaze:

Hemlock now 18" dia. brs. record; N.24°E., 68.7 ft.

S. fir now 29" diam. brs. record; S.55°E., 44.9 ft.

Mark new BTs "CS" "BT" and take measurements to center of
trees at lower blaze:

Hemlock 17" dia. brs. S.27°W., 31.3 ft.

D.Fir 6" dia. brs. N.24½°W., 46.2 ft.

Corner lies approx. 50 ft. east of gravel road.