

TOWNSHIP 30 RANGE 02E POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27 & 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transitman, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Page(s) 21891)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 21, 22, 27, & 28, with brass cap mkd

T30S R2E  
S 21|S 22  
S 28|S 27  
1937

from which

- A fir, 12" dia., bears N.21°E., 35 lks., mkd: T30S R2E S22  
BT.
- A fir, 28" dia., bears S.68°E., 81 lks., mkd: T30S R2E S27  
BT.
- A fir, 20" dia., bears S.66°W., 34 lks., mkd: T30S R2E S28  
BT.
- A fir, 32" dia., bears N.69°W., 61 lks., mkd: T30S R2E S21  
BT.