

TOWNSHIP 30 RANGE 02E POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 34 T29-2E

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch & Lincoln E Wilkes, U.S. Cadastral Engineers, under Special Instructions dated 1920 - (DCSO records Vol. 25 Page(s) 10687 & Vol. 26 Page(s) 11147)

-----  
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor., with brass cap marked

1/4  $\frac{S\ 34}{S\ 3}$   
1923

from which

- A fir, 28" dia., bears N.28°E., 29 lks., mkd: 1/4 S34 BT.
- A maple, 10" dia., bears S.42°E., 28 lks., mkd: 1/4 S3 BT.

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transitman, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Page(s) 21855)

-----  
The 1/4 sec. cor. of secs. 3 & 34, which is an iron post, 1" dia., 10" above ground, firmly set, mkd. and witnessed as described in the official record.