

TOWNSHIP 30 RANGE 02E POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transitman, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Pages 21882-3)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 14, 15, 22, & 23, with brass cap mkd

T30S R2E  
S 15 | S 14  
S 22 | S 23  
1937

from which

- A fir, 33" dia., bears N.70°E., 187 lks., mkd: T30S R2E S14 BT.
- A fir, 38" dia., bears S.62½°E., 188 lks., mkd: T30S R2E S23 BT.
- A fir, 43" dia., bears S.12½°W., 72 lks., mkd: T30S R2E S22 BT.
- A fir, 42" dia., bears N.19°W., 297 lks., mkd: T30S R2E S15 BT.