

TOWNSHIP 30 RANGE 02E POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO dependent resurvey by Leonard Carter, Public Land Surveyor & George F Dawson, Jr. Transitman, under Group No. 175, surveyed April/Aug. 1937 - (DCSO Vol. 56 Page(s) 21874)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground for cor. of secs. 11, 12, 13, & 14 with brass cap mkd:

T30S R2E  
S 11|S 12  
S 14|S 13  
1937

from which

- A fir, 20" dia. bears N.45°E., 61 lks mkd: T30S R2E S12 BT
- A pine, 22" dia., bears S.72°E., 56 lks., mkd: T30S R2E S13 BT.
- A hemlock, 12" dia., bears S.52°W., 20 lks., mkd: T30S R2E S14 BT.
- A fir, 15" dia. bears N.36°W., 76 lks mkd: T30S R2E S11 BT