

TOWNSHIP 30 RANGE 02E POINT IDENTIFIER # 700303

PRIMARY CORNER DESCRIPTION CC Secs. 19 & 30, only; T30-3E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Special Instructions dated Dec. 27, 1920 & Sept. 9, 1927 - (DCSO records Vol. 26 Page(s) 11045-6)

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for closing cor. of secs. 19 & 30, with brass cap mkd

T30S	T30S	
R 2E	S 19	CC
S 24	S 30	
	R 3 E	

1928

from which

- A fir, 40" dia., bears N.56°E., 51 lks., mkd: CC T30S R3E S19 BT.
- A fir, 34" dia., bears S.71°E., 75 lks., mkd: CC T30S R3E S30 BT.

The (1923) corner, by Mensch & Wilkes (Vol. 26 Pg 11140), established for secs. 19, 24, 25 & 30, on line (S.0°13'W., 9.46 chs). We obliterate this corner.

H Raymond fd that there was an error in the 1923 survey by Mensch & Wilkes (see note pg 11026-7) - DCSO, JC 6/6/2012