

TOWNSHIP 30 RANGE 02E POINT IDENTIFIER # 700343

PRIMARY CORNER DESCRIPTION West 1/4 Sec. 19 only, T30-3E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Special Instructions dated Dec. 27, 1920 & Sept. 9, 1927 - (DCSO records Vol. 26 Page(s) 1147)

-----

Set an iron post, 3 ft. long, 1" dia., 18" in the ground to bed rock and build a mound of stone, 2 ft. base, 1 ft. high around the post, for ¼ sec. cor. of sec. 19 only, with brass cap marked

¼  
|  
S 19  
1928

from which

A fir, 7" dia., bears N.4½°E., 43 lks., mkd: ¼ S19 BT.

A fir, 6" dia., bears S.70°E., 7 lks., mkd: ¼ S19 BT.

Obliterate old ¼ sec. cor. without taking a tie to it. The (1923) ¼ corner, by Mensch & Wilkes (Vol. 26 Pg 11141), established for secs. 19 & 24. H Raymond fd that there was an error on the 1923 survey by Mensch & Wilkes (see note pg 11026-7) - DCSO, JC 6/6/2012