

TOWNSHIP 30 RANGE 02E POINT IDENTIFIER # 700504

PRIMARY CORNER DESCRIPTION West CC Secs. 7 & 18 T30-03E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Special Instructions dated Dec. 27, 1920 & Sept. 9, 1927 - (DCSO records Vol. 26 Page(s) 11050)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground for closing cor. of secs. 7 & 18, with brass cap mkd:

T30S		T30S	
R 2E		S 7	CC
S 12		S 18	
		R 3 E	

1928

from which

A fir, 36" dia., bears N.51°E., 377 lks., mkd: CC T30S R3E S7 BT.

A fir, 36" dia., bears S.81½°E., 310 lks., mkd: CC T30S R3E S18 BT.

The (1923) corner, by Mensch & Wilkes (Vol. 26 Pg 11142), established for secs. 7, 12, 13, & 18, on line (S.0°13'W., 10.05 chs and West 62 lks.). We obliterate this corner. H Raymond fd that there was an error in the 1923 survey by Mensch & Wilkes (see note pg 11026-7) - DCSO, JC 6/6/2012