

PRIMARY CORNER DESCRIPTION East 1/4 Cor. Sec. 12 only

Alias	Description

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Special Instructions dated Dec. 27, 1920 & Sept. 9, 1927 - (DCSO records Vol. 26 Page(s) 11051)

Set an iron post, 3 ft. long, 1" dia., 30" in the ground, for ¼ sec. cor. of sec. 12 only, with brass cap mkd.

¼
S 12 |
1928

from which

A fir, 4" dia., bears N.69°W., 18 lks., mkd: ¼ S12 BT.

A pine, 8" dia., bears N.24°W., 35 lks., mkd: ¼ S12 BT.

Obliterate old ¼ sec. cor. without taking a tie to it. The (1923) ¼ corner, by Mensch & Wilkes (Vol. 26 Pg 11143), established for secs. 7 & 12, H Raymond fd that there was an error on the 1923 survey by Mensch & Wilkes (see note pg 11026-7) - DCSO, JC 6/6/2012

Leonard Herzstein, USFS - For: Umpqua National Forest, Tiller Ranger Dist. - June 1999-Sept. 2001 - M168-30 & C.S. 65/84-7

Found - A 1" iron post projecting 6" above the ground, established by GLO Cadastral Engineer, Raymond, in 1928, with a 2½ dia. brass cap attached, stamped (properly mkd) From which, the following original BTs mkd by Raymond in 1928:

A 16" dia. D.Fir, bears N.68°W., 12.2 ft (rec. N.69°W., 11.88 ft), with a healed single blaze.

A roothole with a downed 18" dia. sugar pine log alongside, bears N.27°30'W., 23.1 ft (rec. N.24°W.). I open a healed single blaze and find scribe marks "¼ S12 BT"

New BOs- A 12" dia. D.Fir, bears S.43°30' W., 8.5 ft. I scribe "¼ S12 BT" on a single blaze.

A 6-foot brown Carsonite post driven 2 ft in the ground, bears N.14°W., 1.8 feet, with "Land Survey Monument" decal attached.

Note - I found the magnetic declination to be 15° East. The corner is on a flat spur ridge, sloping East.