

TOWNSHIP 30 RANGE 02E POINT IDENTIFIER # 700604

PRIMARY CORNER DESCRIPTION CC, Sec. 6 & 7; T30-3E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,
under Special Instructions dated Dec. 27, 1920 & Sept. 9,
1927 - (DCSO records Vol. 26 Page(s) 11052)

Set an iron post, 3 ft. long, 2" dia., 30" in the ground for
closing cor. of secs. 6 & 7, with brass cap mkd:

	T30S	
T30S		T30S
	S 6	
R 2E		CC
	S 7	
S 1		R 3 E

1928

from which

A fir, 15" dia., bears N.25°E., 27 lks., mkd: CC T30S R3E
S6 BT.

A fir, 45" dia., bears S.68°E., 62 lks., mkd: CC T30S R3E
S7 BT.

The (1923) corner, by Mensch & Wilkes (Vol. 26 Pg 11143),
established for secs. 1, 6, 7 & 12, on line (S.0°13'W., 10.24
chs). We obliterate this corner.

H Raymond fd that there was an error in the 1923 survey by
Mensch & Wilkes (see note pg 11026-7) - DCSO, JC 6/7/2012