

TOWNSHIP 30 RANGE 02E POINT IDENTIFIER # 700644

PRIMARY CORNER DESCRIPTION West 1/4 Sec. 6; T30-3E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,
under Special Instructions dated Dec. 27, 1920 & Sept. 9,
1927 - (DCSO records Vol. 26 Page(s) 11053)

Set an iron post, 3 ft. long, 1" dia., 30" in the ground, for
¼ sec. cor. of sec. 6 only, with brass cap mkd:

 |
 | ¼
 | S 6
 |
 1928

from which

 A pine, 40" dia., bears N.78°E., 40 lks., mkd: ¼ S6 BT.

 A fir, 20" dia., bears S.15°E., 75 lks., mkd: ¼ S6 BT.

Obliterate old ¼ sec. cor. without taking a tie to it.
The (1923) ¼ corner, by Mensch & Wilkes (Vol. 26 Pg 11144),
established for secs. 1 & 6, H Raymond fd that there was an
error on the 1923 survey by Mensch & Wilkes (see note pg
11026-7) - DCSO, JC 6/8/2012