

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31 only, (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6868)

Set a granite stone 15x12x5 ins., 10" in the ground for closing cor. of secs. 30 and 31, mkd. C C on E. with 5 grooves on N. and 1 groove on S. face, from which
A Maple 15" dia., bears N.56½°E., 27 lks. dist. mkd. T30S R2W S30 BT.
A Maple 10" dia., bears S.58°E., 37 lks. dist. mkd. T30S R2W S31 BT.

A. Boyer, Deputy Co. Surveyor - Geo. Stone and Donald Stone, Witnesses - Jan. 30, 1939 - C.S. File 16/11

Maple tree to SE. gone and rock originally set for corner loose and out of place.
Set a 3/4" Pipe from Maple tree to the NE. and put rock back in place as well as possible and marked a new BT:
A 12" Maple S.41½°E., 38 ft. mkd. C C S31 T30S R2W CS BT

Douglas Co. Surveyors Office - James Byron, Deputy - Godfrey and Bilow, crew - May 7, 1958 - C.S. File 49/86

I find closing corner for 30 and 31 pipe and BTs OK, as recorded by Boyer in 1939.

Ron Quimby - Crew: N. Fromdahl & L. Heddens - 6/2020 - C.S. File 65/106-30

Found - 3/4" IP
Brass cap sec. cor. 25 & 36 only N.1°W., 46.2 ft.
New - 8" Hemlock N.59°E., 4.1 ft scribed T30S R2W S30 BT
7" Hemlock N.83°W., 8.5 ft marked X
Alum posts 5' north and 10' East
Note - Compass decl. 15½°E.