

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24 & 25, T30-3

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6751)

-----  
Set post cor. secs. 19, 30, 24 and 25, from which  
An Oak 12" dia., bears N.38°W., 141 lks. dist.  
An Oak 12" dia., bears N.45°E., 59 lks. dist.  
An Oak 15" dia., bears S.54°W., 37 lks. dist.  
An Oak 12" dia., bears S.74°E., 56 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6772) and (duplicate desc. on Pgs. 6904-05)

-----  
I find the 4 witness trees to the cor. to secs.19, 24, 25 and 30, but the corner has been destroyed. At cor. point, I set an Oak post, 4 ft. long, 4" sq., 24" in the ground, for sec. cor., marked T30S S19 on NE.; R2W S30 on SE.; R3W S25 on SW.; and S24 on NW. faces with 4 notches on N. and 2 notches on S. edges, from which  
An Oak 12" dia., (15" now) bears N.45°E., 59 lks. dist. mkd. T30S R2W S19 BT.  
An Oak 12" dia., (15" now) bears S.74°E., 56 lks. dist. mkd. T30S R2W S30 BT.  
An Oak 15" dia., bears S.54°W., 37 lks. dist. mkd. T30S R3W S25 BT.  
An Oak 12" dia., (18" now) bears N.38°W., 141 lks. dist. mkd. T30S R3W S24 BT.

Germond - Wit: Goltzor and Gorus - Aug. 1916 - C.S. File 1/33 and Vol. 3 Page 19

-----  
Set 1¼" iron bar in ground. Old Oak witness trees all in fair condition. Did not mark new trees.

G. J. Wenderoth, Deputy Co. Surveyor - Frank Loso; John H. Howell, witnesses - March 1948 - C.S. File 30/121

-----  
Found 1" Iron bar and old BTs.  
15" Oak N.45°E., 38.9 ft.  
15" Oak N.74°E., 36.9 ft.  
15" Oak S.54°W., 24.2 ft.  
18" Oak N.38°W., 93.0 ft.  
All BTs in poor shape so mark new BTs:  
24" Madrona N.2°26'E., 30.9 ft.  
18" Madrona N.49°50'W., 36.0 ft.  
16" Madrona S.64°32'W., 18.2 ft.  
16" Madrona S.31°25'E., 9.3 ft. (Cont. Next Page)

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24 & 25, T30-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Survey by Howard Johnstone - For: Roseburg Resources Co. -  
Dec. 30, 1985 - M 100-21

-----  
Found - 3/4" Drill steel.  
18" Madrone snag bears N.49°50'W., 26.0 ft.  
24" Madrone snag bears N.2°26'E., 30.9 ft.  
16" Madrone snag bears S.31°25'E., 9.3 ft.  
16" Madrone stump bears S.64°32'W., 19.2 ft. (Rec.  
18.2 ft. dist.)  
15" Oak bears S.54°W., 24.4 ft., snag.  
Set a 5/8" Iron rod and alum. cap mkd. "LS 498".  
New BTs- 5" Fir bears N.46°W., 24.0 ft., scribed.  
Scribed a 6" Madrone, bears N.46°E., 43.8 ft.  
Scribed a 6" Madrone, bears S.58°E., 21.3 ft.  
Scribed a 5" Madrone, bears S.22½°W., 12.7 ft.

Tony Hostetter - For: Seneca Jones Timber Co. - April 2003 -  
M141-79

-----  
Found - 1985 alum. cap on 5/8" rod as described by H.  
Johnstone. (M100-21) from which:  
Steel fence post bears North 0.3 ft.  
18" Madrone snag w/tag, @ N.49°50'W., is down.  
All other BTs by Johnstone are gone.  
New BTs- 6" Madrone, bark scribed "S19 SW BT", bears N.5°E.,  
28.3 ft. to spike.  
4" Madrone, bark scribed "S25 NE BT", bears S.26°W.,  
14.7 ft.  
5" Madrone, bark scribed "S25 NE BT", bears S.63°W.,  
31.6 ft.