

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6751)

Set ¼ sec. post, from which
A Laurel 24" dia., bears S.38°E., 40 lks.
A Maple 6" dia., bears N.60°W., 50 lks.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6782) and (duplicate info. on Page 6914)

I find the ¼ sec. cor. greatly decayed with marks nearly obliterated, 24 lks. West of my line, I find one witness tree. At cor. point, I set a Cedar post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on W. face, from which
A Laurel 24" dia., (now 30") bears S.38°E., 40 lks. dist. mkd. ¼ S BT. This is the original witness tree.
I Mark:
A Fir 8" dia., bears S.50°W., 18 lks. dist. mkd. ¼ S BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page 6786 and Pgs. 6794-95)

(Page 6786)
Fd. ¼ sec. cor. witnessed as described by the surveyor general.
(Pages 6794-95)
I re-establish the old ¼ sec. cor. in its original position as the ¼ sec. cor. on E. bdy. sec. 24, T30S R3W, only, as follows:
No stones available, Set a Cedar post 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. on E. bdy. sec. 24, marked ¼ S24 on W. face, from which
A Fir 10" dia., bears S.50°W., 18 lks. dist. mkd. ¼ S24 BT
A Fir 28" dia., bears N.88°W., 36 lks. dist. mkd. ¼ S24 BT

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: Fred Seymour - March 14, 1951 - C.S. File 40/302

Determined by O.B.T.:
A Fir stump 39" dia., bears N.88°W., 23.7 ft. dist. I chopped this stump out and found scribe.
A Laurel snag 36" dia., bears S.38°E., 26.4 ft. dist.
I remark both O.B.T.s.
At corner point, Set wood stake, from which
(Cont. Next Page)

