

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 100512

PRIMARY CORNER DESCRIPTION Line Tree Secs 7; & 12 T30-3W

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6784) and (duplicate info. on Pages 6917)

A fir, 40" dia., on line marked with 2 notches on N & S sides.

Greg Lang - For: Rome Creek Timber III LLC - July 2013 - C.S. File 65/79-12A & E

Found - D.Fir line tree (now 49") in proper relative position. Tree has two hack marks on south side. A reference monument set on the Section line bears S.0°33'53"E., 3.00' from the corner tree. Said monument is a 5/8"x18" iron rod with plastic cap marked "LANG SURVEYING" and is driven in a large root at the base of the line tree.

New BTs- 8" D.Fir bears N.7½°W., 20.30' scribed "LT S12 BT"
8" I.Cedar bears S.59°E., 11.50' scribed "LT S7 BT"

Note - Bearings are to the center of the trees & distances are measured to a spike in the side of the trees. Corner lies in a relatively flat area between two drainages.