

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec Cor for 6 & 7; 1 & 12, T30-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6786) and (duplicate info. on Page 6918)

Set a stone 16x12x12 ins., 12" in the ground for cor. to secs. 1, 6, 7 and 12, marked with 1 notch on N. and 5 notches on S. edges; from which

- A Fir 30" dia., bears N.44°E., 97 lks. mkd. T30S R2W S6 BT
- A Fir 24" dia., bears S.45°E., 20 lks. mkd. T30S R2W S7 BT
- A Fir 12" dia. bears S.33°W., 60 lks. mkd. T30S R3W S12 BT
- A Fir 33" dia. bears N.67½°W., 19½ lks mkd. T30S R3W S1 BT

Cor. Fd. and used in GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6787 and Pg. 6791)

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel, crew - Jan. 1963 - C.S. File 52/138-38

Found all orig. BTs. All check record. SW. BT shows scribing. NW. BT down.
Set brass cap at cor. and at hub with tack, set recently.
Marked cap: County Surveyors Office

	T	30	S	
	S	1	S	6
R3W	S	12	S	7
		1963		

New BTs- 9" Fir bears N.4°W. 14.2 ft scribed S1 T30S R3W CS BT
12" Chinquapin bears N.30°E., 4.4 ft. scribed T30S R2W S6 CS BT.

Fd. and used in BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #705, surveyed Sept/Oct 1970 - (DCSO records Vol. 35 Page(s) 14513-14)

Fd. and used in BLM resurvey by Peter Peterson and Daniel Berry under Group #749, surveyed July/Aug. 1971 - (DCSO records Vol. 36 Page(s) 14913-14)

Ron Quimby - Crew: N. Fromdahl, R Heichel & R Vincent - 1/2018 - C.S. File 65/101-18

Found - DCSO brass cap (properly mkd)
16"x12"x12" stone no marks visible.
16" chinquapin N.30°E., 4.4 good scar.
44" Fir S.45°W., 13.2 ft. good scar.
28" Fir S.33°W., 39.6 ft. good scar.
34" Fir N.67°W., 12.9 ft. good scar (down cont.)

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12, T30-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

12" Fir snag N.14°W., 14.2 ft. good scar.
New - 8" Fir N.87°W., 30.7 ft. scribed T30S R3W S1 BT
Note - Corner is SE 300'± from switchback in road near top
of ridge.
Compass decl. 15½°E.