

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION NW Cor. Sec. 6 (NW Tsp. Cor)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 15 Page(s) 6203) and (duplicate pg. #6826)

Intersect E. boundary T29S R3W, 6.16 chs. S. of ¼ sec. cor. in E. bdy. Sec. 36.
Set a slate stone 18x10x10 ins., 12" in the ground for closing cor. of Tps. 29 and 30 S., R. 2 W. marked C C on E. with 6 grooves on N., S., and E. faces, from which
 A Hemlock 12" dia., bears N.44°E., 22 lks. dist. marked T29S R2W S31 BT.
 A Hemlock 10" dia., bears S.40½°E., 48 lks. dist. mkd. T30S R2W S6 BT.

GLO resurvey by Elmer F. Strickler, U.S. Transitman under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6222-23)

Intersect the closing cor. of Tps. 29 and 30 S., R. 2 W., which is a slate stone, firmly set, marked and witnessed as described by the surveyor general. I perpetuate this cor., as follows; alongside the old cor.
Set an iron post, 3 ft. long, 3" dia., 24" in the ground, for closing cor. of Tps. 29 and 30 S., R 2 W., with brass cap marked
 T29S
 T29S | R2W
 S36 | S31 CC
 S6
 R3W | T30S
 1917
from which
 A Hemlock 12" dia., bears N.44°E., 22 lks. dist., mkd. T29S R2W S31 BT. (Old BT)
 A Hemlock 10" dia., bears S.40°30'E., 48 lks. dist., mkd. T30S R2W S6 BT. (Old BT)

Fd. and Used in BLM resurvey by Peter Peterson and Daniel Berry under Group #749, surveyed July/Aug. 1971 (DCSO records Vol. 36 Page(s) 14921)

Fd. OK, Nov. 1984 by H. Johnstone - M 97-65

David Edwards - For: Roseburg Resources - Oct. 2016 - M172-56

Found - 1917 GLO Brass capped iron pipe.
 A 20" dia. Hemlock high stump with H.B. bears N.44°E., 14.5'
continued next page

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION NW Cor. Sec. 6 (NW Tsp. Cor)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A 22" dia. Hemlock high stump with H.B. bears
S.40½°E., 31.7'
NEW BTs- A 9" dia. Cedar scribed T29S R2W S31 BT" bears
N.35°E., 28.4'
An 8" dia. Fir scribed T30S R2W S6 BT" bears
S.35°E., 24.8'
A 6 ft steel post is set 2 ft north.