

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 138500

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 18 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6833-34)

-----  
No stones available. Set a Sugar Pine post 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. on N. bdy. sec.18, marked ¼ S18 on S. face, from which  
A Hemlock 5" dia., bears S.21°E., 60 lks. dist. mkd. ¼ S18 BT.  
A Fir 18" dia., bears S.20°W., 39 lks. dist. mkd. ¼ S18 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S.A. Bilow, crew - Jan. 30, 1959 - C.S. File 49/86-4

-----  
Found - Orig. 18" now 26" Fir stump S.31°E., 25.7 ft., shows good scribing "S18".  
Orig. 5", now down, 8" Hemlock, shows good scribing "S18 BT", bears S.21°E., 39.6 ft.  
1" Iron pipe 3.0 ft. above ground at corner.  
I SET 3/4" Iron rod alongside iron pipe.  
New BTs- 17" R.Fir bears S.62°W., 77.5 ft. scribed ¼ S18 CS BT.  
24" Sugar Pine bears N.50°W., 3.5 ft. scribed ¼ S18 CS BT.

Fd. OK, Nov. 1968 by DCSO, J.Powell - C.S. File 54/73-47A

Survey by Ron Geisler, LS #1988 - For: Champion International Corp. - April/May 1986 - M 100-78

-----  
Corner Report Only  
Found - 1963 DCSO brass cap and iron pipe.  
32" Sugar Pine bears N.63°W., 3.5 ft. (Rec. N.50°W), closed face.  
10" Fir bears S.75°W., 23.8 ft., closed face.  
Unrecorded 9" Fir bears S.85½°E., 41.5 ft. (1970 BLM tag mkd. 40.9'.) Closed face.  
3/4" Iron rod alongside brass cap/iron pipe and a 1" Iron pipe which bears S.40°W., 0.80' from the cap. (Found in 1959)

BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #705, surveyed Sept/Oct 1970 - (DCSO records Vol. 35 Page(s) 14516)

-----  
The ¼ sec. cor. of sec. 18 only, monumented with an iron pin  
(Cont. Next Page)

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 138500

PRIMARY CORNER DESCRIPTION No. 1/4 cor. for Sec. 18 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

3/4" dia., firmly set, projecting 12" above ground, from which the original bearing tree:

A Fir stump 34" dia., bears S.21°W., 39 lks. dist., with fragmentary scribe marks visible on open blaze.

and a tree of which I have no record:

A Pine 32" dia., bears N.50°W., 5 lks. dist. with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, with brass cap mkd:

T 30 S R 2 W

¼

S 18

1970

from which a new bearing tree

A Fir 8" dia., bears S.75°W., 36 lks. dist. mkd. ¼ S18 BT.  
Reset the iron pin alongside the iron post.