

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 139300

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 30 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6771)

-----  
Set ¼ sec. post, from which  
A Fir 12" dia., bears S.25°E., 29 lks.  
A Laurel 24" dia., bears N.40°E., 20 lks.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6801 and 6807)

-----  
(Page 6801)  
The ¼ sec. cor. bearly obliterated. No trace of the post is found and the bearing trees are deeply overgrown.  
(Page 6807)  
I re-establish the old ¼ sec. cor. in its original position as the ¼ sec. cor. on N. bdy. sec. 30 only as follows:  
No stones available. Set a Fir post 3 ft. long, 4" sq., 24" in the ground, marked ¼ S30 on S. face, from which  
A Fir 18" dia., bears S.25°E., 30 lks. dist. mkd. ¼ S30 BT  
A Madrone 12" dia., bears S.22°W., 32 lks. dist. mkd. ¼ S30 BT.  
Marks on former bearing tree referring to sec. 19 are obliterated.

Douglas Co. Surveyors Office - John M. Powell, F. Jones & W. Penley, crew - Oct/Nov. 1968 - C.S. File 54/73-17

-----  
Found - 18" D.Fir, now down, S.25°E., 19.8 ft., opened for scribe "T".  
12" laurel now 14" and broken, S.22°W., 21.1 ft.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 30 S R 2 W  
¼ \_\_\_\_\_  
S 30  
1968  
New BTs- 6" Y.Pine S.4°W., 8.1 ft. mkd. S30 ¼ CS BT.  
5" D.Fir S.35°E., 6.4 ft. mkd. ¼ S30 CS BT.  
Corner lies 68.0 ft. West of ¼ cor. to sec. 19.

Fd. OK, Dec.1985/Feb. 1986 by H. Johnstone - M 100-21