

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 31 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6814)

Set a granite stone 15x8x6 ins., 10" in the ground for ¼ sec. cor. on N. bdy. Sec. 31, marked ¼ on S. face, from which
A Fir 20" dia., bears S.55°E., 56 lks. dist. mkd. ¼ S31 BT.
A Maple 8" dia., bears S.39°W., 15 lks. dist. mkd. ¼ S31 BT.

Corner Report by James Byron, Doug. Co. Surveyors Office - May 7, 1958 - C.S. File 49/86

The N. ¼ corner sec. 31 has good rock, with + on top and 4 on S. side. Also, both BTs OK.

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - Dec. 30, 1985 - M 100-21

Found - Original stone and square post.
50" Fir bears S.62°E., (Rec. S.55°E.) 37.0 ft. dist. with healed blaze. (Orig.)
8" Maple, split snag, bears S.32°W., (Rec. S.39°W.) 9.9 ft. dist.

Ron Quimby - Crew: N. Fromdahl & L. Heddens - 6/2020 - C.S. File 65/106-28

condition report only
Found - Orig. Stone approx 15x8x6 with + on top (see picture with CS file)
52" Fir S.62°E., 37.0 ft. good scar.
15" split maple S.32°W., 9.9 ft.
Alum. cap on 5/8" IR per M100-21 bears West 58.04 ft
Note - Compass decl. 15½°E.